

Material Safety Data Sheet

0646 Masonry & Concrete Repair – Acrylic – Gray –
All labels except ACE

MSDS No. 0050 Rev. 6

Emergency Phone No.
(918)825-5744

SECTION 1 – PRODUCT NAME & MANUFACTURER INFORMATION

PRODUCT NAME	Masonry & Concrete Repair Caulk – Acrylic Latex - Gray
MANUFACTURER'S NAME & TELEPHONE NUMBER	Red Devil, Inc. 918-825-5744
STREET ADDRESS	4175 Webb Street
CITY / STATE / ZIP	Pryor, Oklahoma 74361

SECTION 2 – COMPOSITION / HAZARDOUS INGREDIENTS

	%	TLV	PEL	UNITS
PRODUCT CONSISTS OF:				
Calcium Carbonate ** (1317-65-3)	<60	10	15	mg/m3
Acrylic Terpolymer Emulsion (mixture)	<30	NE	NE	
Benzoate Ester (proprietary)	<6	NE	NE	
Petroleum Distillate (64742-48-9)	<1.2	100	100	ppm
Ammonium Hydroxide (7664-41-7)	<0.25	25	50	ppm
Titanium Dioxide (13463-67-7)	<1	10	10	mg/m3
Non-hazardous ingredients*	<25	NA	NA	
*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). Calculated VOC: <3% (40-50 g/L). CARB Compliance: Yes. Prop 65 Ingredients: Yes (See Section 16)				

SECTION 3 – HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF ENTRY	<input checked="" type="checkbox"/> Skin Contact	<input checked="" type="checkbox"/> Skin Absorption	<input type="checkbox"/> Eye Contact	<input checked="" type="checkbox"/> Inhalation	<input type="checkbox"/> Ingestion
EMERGENCY OVERVIEW	Textured gray paste w/ slight ammoniacal odor. Harmful if swallowed. May cause eye, nose, skin, respiratory tract & throat irritation.				
EFFECTS OF OVEREXPOSURE	May cause eye, skin, nose, throat & respiratory tract irritation.				
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	None known.				

SECTION 4 – FIRST AID MEASURES

SKIN CONTACT	Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.
EYE CONTACT	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.
INHALATION	Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.
INGESTION	DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION 5 – FIRE FIGHTING MEASURES

FLAMMABLE Yes No

EXTINGUISHING MEDIA Carbon Dioxide, Dry Chemical, Foam

FLASHPOINT (°F) & METHOD >200F (Seta Closed Cup)

UPPER EXPLOSIVE LIMIT (% BY VOLUME) NE

LOWER EXPLOSIVE LIMIT (% BY VOLUME) NE

AUTOIGNITION TEMPERATURE (°F) NE

UNUSUAL FIRE & EXPLOSION HAZARDS None known.

SPECIAL FIREFIGHTING PROCEDURES Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PROCEDURES Wear proper protective equipment (Section 8). Use absorbent material or scrape up dried material & place in approved container.

SECTION 7 – HANDLING & STORAGE

HANDLING PROCEDURES & EQUIPMENT Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing.

STORAGE REQUIREMENTS Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120F. Store away from caustics & oxidizers.

SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

RESPIRATORY In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator w/ organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits.

EYEWEAR Goggles or safety glasses w/ side shields.

CLOTHING / GLOVES Rubber gloves (Neoprene recommended). Other protective equipment not required under normal use.

HYGENIC PRACTICES Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of workday.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE Paste ODOR & APPEARANCE Mild acrylic/v. slight ammoniacal odor. Textured gray paste.

SPECIFIC GRAVITY Approximately 1.50 to 2.0 VAPOR DENSITY (AIR=1) Heavier than air

EVAPORATION RATE NE BOILING RANGE (°F) NE

pH Approximately 7 to 9 SOLUBILITY IN WATER Appreciable, before cure.

VAPOR PRESSURE (MM Hg) NE %/WT VOLATILE (TNV) < 20

SECTION 10 – STABILITY AND REACTIVITY

STABILITY Yes No Stable under normal conditions.

INCOMPATIBILITY Yes No Incompatible w/ strong bases & oxidizers.

CONDITIONS TO AVOID Excessive heat & freezing.

HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS Hazardous polymerization will not occur under normal conditions. Normal decomposition products, ie: COx, NOx.

SECTION 11 – TOXICOLOGICAL INFORMATION / CARCINOGENICITY

ACGIH	Small amount of Silica, crystalline present in Calcium Carbonate & trace residual Formaldehyde present in base emulsion are suspected human carcinogens. Monomers used in base emulsions are confirmed animal carcinogens w/ unknown relevance to humans.
OSHA	Trace residual Formaldehyde present in base emulsion viewed as a possible cancer hazard. Monomer used in base emulsion, a cancer hazard.
IARC	Trace residual Formaldehyde: Human carcinogen. Monomers in base emulsion: Possible carcinogen.
NTP	Silica, crystalline, present in small amount in Calcium Carbonate Filler: Known carcinogen. Trace residual Formaldehyde & various monomers used in polymerization of base emulsion: Anticipated carcinogens.
DATA WITH POSSIBLE RELEVANCE TO HUMANS	Product contains trace amounts of residual Formaldehyde. OSHA & NTP identify Formaldehyde as a potential carcinogen. IARC identifies Formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, w/ human significance unknown. Rats have shown carcinogenic effects in respiratory system. Risk should be minimal when used w/ adequate ventilation. Maintain adequate ventilation to prevent exposure above OSHA exposure limits. Product contains trace amounts of Acrylonitrile. It is exempt from OSHA Acrylonitrile Standard 29 CFR 1910.1045. Acrylonitrile has been classified by IARC as possibly carcinogenic to humans, by OSHA as carcinogenic & by NTP as anticipated to be a human carcinogen.

SECTION 12 – ECOLOGICAL INFORMATION

AQUATIC TOXICITY	Not known or expected under normal use.
-------------------------	---

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL	Dispose of material in accordance w/ Federal, State & Local regulations.
EPA WASTE CODE IF DISCARDED (40CFR Sec.261)	None.

SECTION 14 – TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION	Shipping information applicable for domestic for domestic ground transport only. Different categorization may be necessary if shipped via other modes of transportation &/or to non-domestic destinations. PRODUCT NOT REGULATED BY DOT.
-------------------------------------	--

SECTION 15 – REGULATORY INFORMATION

CERCLA – SARA HAZARD CATEGORY	Immediate health hazard; chronic health hazard.	U.S. STATE REGS	See Section 16.
SARA 313	None.	TSCA	All ingredients either on TSCA Inventory or exempt. Product contains no TSCA 12(B) materials, if exported from the U.S.

SECTION 16 – OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

Prop 65 Ingredients: Crystalline Silica, Formaldehyde, various monomers used in polymerization of base emulsions. **NJ Right-to-Know:** (Top 5 Ingredients): Calcium Carbonate (1317-65-3), Base Acrylic Emulsion Blend (mixture), Benzoate Ester (proprietary), Water (7732-18-5), Petroleum Distillate (64742-48-9). **Pennsylvania Right-to-Know (Non-Haz @ >3%):** Water (7732-18-5). **Ingredients Known to State of California to cause cancer &/or developmental toxicity &/or reproductive toxicity:** Acrylonitrile (107-13-1), Ethyl Acrylate (140-88-5), Formaldehyde (50-00-0). Titanium Dioxide (13463-67-7) added to Massachusetts Right to Know List, Minnesota Hazardous Substance List, New Jersey Right to Know List, Pennsylvania Right to Know List & Rhode Island Hazardous Substance List. **HMIS Ratings:** Health: 1, Flammability: 1, Reactivity: 0, Personal Protection: X. Color dispersion may contain carbon black.

LEGEND: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act

Reviewed By: <u>Larry G. Brandon</u>	VP Technology & General Manager	March 12, 2009
NAME	TITLE	DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.